889006-01 - 889** Safety group, straight model, 3/4" brass seat

Product Data Sheet 2026/11/23

A Comap Safety Group may be fitted to all sorts of storage water heaters under the terms of EN 1487.



Technical Specifications

- Maximum system pressure: 5.25 bar.

If the pressure in the supply line exceeds this value, a pressure-reducing valve must be fitted before (upstream from) the safety group.

- Minimum system pressure: 0.2 bar.
- Maximum system supply-line temperature: 65 °C.
- Minimum system temperature: network's cold water.

Description	889** Safety group, straight model, 3/4" brass seat
Order Code	889006-01
GTIN	3430650084377
Model	Comap Safety Groups
Dimensions	3/4"
Set pressure [bar]	7

* DN15 (1/2" connection adapter included)
** Conformity to the EN 1487





Classification General Data

Etim Group	Measuring and control devices
Etim Class	Safety valve
Product Name	889 Safety valve straight NC 7bar 3/4
Brand	Flamco
Product Type	Safety Groups
Order Code	889006-01
GTIN	3430650084377

© 2026 Aalberts hfc B.V. All rights reserved. We reserve the right to change designs and technical specifications of our products.

Find more information online:

Installation and operating instructions
NF Certificate
Certificate ACS

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 20 210 34 97
E nl.info@aalberts-hfc.com
I comap.aalberts-hfc.com/nl

© 2026 Aalberts hfc B.V. All rights reserved. We reserve the right to change designs and technical specifications of our products.