# 889216 - 889** Safety group stainless steel, right-angled model, 3/4"

Product Data Sheet 2026/11/23

A Comap Safety Group may be fitted to all sorts of storage water heaters under the terms of EN 1487.



## Technical Specifications

- Maximum system pressure: 5.25 bar.

If the pressure in the supply line exceeds this value, a pressure-reducing valve must be fitted before (upstream from) the safety group.

- Minimum system pressure: 0.2 bar.
- Maximum system supply-line temperature: 65 °C.
- Minimum system temperature: network's cold water.

| | |
|---|---|
| Description | 889** Safety group stainless steel, right-angled model, 3/4" |
| Order Code | 889216 |
| GTIN | 3430650433953 |
| Model | Comap Safety Groups |
| Dimensions | 3/4" |
| Set pressure [bar] | 7 |

* DN15 (1/2" connection adapter included)
** Conformity to the EN 1487





## Classification General Data

| | |
|---|---|
| **Etim Group** | Measuring and control devices |
| **Etim Class** | Safety valve |
| **Product Name** | 889 Safety valve elbow Inox 3/4 |
| **Brand** | Flamco |
| **Product Type** | Safety Groups |
| **Order Code** | 889216 |
| **GTIN** | 3430650433953 |



© 2026 Aalberts hfc B.V. All rights reserved. We reserve the right to change designs and technical specifications of our products.

## Find more information online:

Installation and operating instructions
NF Certificate
Certificate ACS

Fort Blauwkapel 1
1358 DB, Almere - nl

**T** +31 20 210 34 97
**E** nl.info@aalberts-hfc.com
**I** comap.aalberts-hfc.com/nl



© 2026 Aalberts hfc B.V. All rights reserved. We reserve the right to change designs and technical specifications of our products.