27930 - Flexcon KSG 3/4 EcoPlus

Product Data Sheet 2026/11/22

A Flexcon KSG boiler connection assembly is suitable for venting and safeguarding sealed heating or cooling systems including those with glycol-based additives (maximum 50%).



Advantages

- The Flexcon KSG boiler connection assembly inclusive of EPP insulation.
- With a Flexvent automatic air vent, with valve sleeve, Flamco safety valve, pressure gauge with valve sleeve.

Technical Specifications

- Minimum/Maximum working temperature: -10 °C / 90 °C.
- Suitable for addition of glycol-based anti-freeze up to 50%.
- Safety valve: ½" x 3/4", 2.5 bar (110 kW).
- Flexvent 3/8" with shut-off valve.
- Pressure gauge: Ø 61 mm, 6.0 bar with shut-off valve.
- Insulation: material EPP - color: black.

Description	Flexcon KSG 3/4" 2,5bar EcoPlus
Order Code	27930
GTIN	8712874279308
Model	Flexcon KSG Ecoplus
Set pressure [bar]	2.5
Connection	Rp $^{3}/_{4}$"
Heating capacity [kW]	110





Classification General Data

Etim Group	Pressurization and expansion systems
Etim Class	Expansion tank connection group
Product Name	None
Brand	Flamco
Product Type	Prescor Safety sets
Order Code	27930
GTIN	8712874279308

© 2026 Aalberts hfc B.V. All rights reserved. We reserve the right to change designs and technical specifications of our products.

Find more information online:

Installation and operating instruction
Flexcon KSG Ecoplus DWG
Flexcon KSG Ecoplus STEP
Flexcon KSG Ecoplus RFA
Packaging data

Fort Blauwkapel 1
1358 DB, Almere - nl

T +31 (0)36 52 62 300
E info@aalberts-hfc.com
I flamco.aalberts-hfc.com

© 2026 Aalberts hfc B.V. All rights reserved. We reserve the right to change designs and technical specifications of our products.